

# ASROCK MSI B250M GAMING PRO uATX B250 1151 DDR4 SATAIII M.2 USB 3.0

: 86,00€

## Déscription du produit

CPU • Supports 6th/ 7th Gen Intel® Core™ i3/i5/i7 processors, and Intel® Pentium® and Celeron® processors for Socket LGA1151 \* This function will be supported depend on the CPU. Chipset • Intel® B250 Chipset Main Memory • 2 x DDR4 memory slots, support up to 32GB - 7th Gen processors support DDR4 2400/ 2133 MHz\* - 6th Gen processors support DDR4 2133 MHz\* • Dual channel memory architecture \* Please refer [www.msi.com](http://www.msi.com) for more information on compatible memory. Slots • 1 x PCIe 3.0 x16 slot (supports x16 mode) • 2 x PCIe 3.0 x1 slots Onboard Graphics • 1 x HDMI™ port, supports a maximum resolution of 4096x2160@30Hz(7th CPU), 4096x2160@24Hz(6th CPU), 2560x1600@60Hz • 1 x DVI-D port, supports a maximum resolution of 1920x1200@60Hz • 1 x VGA port, supports a maximum resolution of 2048x1536@50Hz, 2048x1280@60Hz, 1920x1200@60Hz Storage • Intel® B250 Chipset • 6 x SATA 6Gb/s ports • 1x M.2 slot (Key M)\* - Supports up to PCIe 3.0 x4 and SATA 6Gb/s - Supports 2242/ 2260 /2280 storage devices - Intel® Optane™ Memory Ready - Support PCIe 3.0 x4 NVMe U.2 SSD with Turbo U.2 Host Card\*\* \*The SATA1 connector will be unavailable when an M.2 SSD module has been installed in the M.2\_1 slot. \*\* The Turbo U.2 Host Card is not included, please purchase separately. USB • Intel® B250 Chipset - 6 x USB 3.1 Gen1 (SuperSpeed USB) ports (3 Type-A & 1 Type-C ports on the back panel, 2 ports available through the internal USB connector) - 6 x USB 2.0 (High-speed USB) ports (2 ports on the back panel, 4 ports available through the internal USB connector) Audio • Realtek® ALC887 Codec - 7.1-Channel High Definition Audio LAN • 1 x Intel® I219-V Gigabit LAN controller Internal I/O Connectors - 1 x 24-pin ATX main power connector - 1 x 8-pin ATX 12V power connector - 6 x SATA 6Gb/s connectors - 2 x USB 2.0 connectors (supports

additional 4 USB 2.0 ports) - 1 x USB 3.1 Gen1 connector (supports additional 2 USB 3.1 Gen1 ports) - 1 x 4-pin CPU fan connector - 2 x 4-pin system fan connectors - 1 x Front panel audio connector - 2 x Front panel connectors - 1 x TPM module connector - 1 x Chassis Intrusion connector - 1 x Serial port connector - 1 x Parallel port connector - 1 x RGB LED connector - 1 x Clear CMOS jumper

Back Panel I/O Ports - 1 x PS/2 keyboard port - 1 x PS/2 mouse port - 1 x VGA port - 1 x DVI-D port - 1 x HDMI port - 2 x USB 2.0 Type-A ports - 3 x USB 3.1 Gen1 Type-A ports - 1 x USB 3.1 Gen1 Type-C port - 1 x LAN (RJ45) port - 3 x audio jacks

Dimension • 9.6 in. x 8.1 in. (24.3 cm x 20.6 cm) • m-ATX Form Factor

Mounting • 6 mounting holes

1. Les caractéristiques sont sujettes à certaines modifications sans préavis. Renseignez-vous auprès de votre revendeur afin de connaître les caractéristiques exactes.