

ASROCK MSI B250M MORTAR INTEL B250 uATX Socket 1151 4xDDR4 6xSATA3

: 106,00€

Déscription du produit

CPU • Supports 7th/6th Gen Intel® Core™ i3/i5/i7 processors, and Intel® Pentium® and Celeron® processors for Socket LGA1151 * This function will be supported depend on the CPU. Chipset • Intel® B250 Chipset Main Memory • 4 x DDR4 memory slots, support up to 64GB - 7th Gen processors support DDR4 2400/2133 MHz*/ ** - B250 chipset + 6th Gen processors support DDR4 2133 MHz*/ ** • Dual channel memory architecture • Supports Intel® Extreme Memory Profile (XMP)** * Please refer to www.msi.com for more information on compatible memory. **DDR4 memory modules can only run at maximum of 2400 MHz for 7th Gen processors and 2133 MHz for 6th Gen processors on XMP mode. Slots • 2 x PCIe 3.0 x16 slots (support x16/x4 mode) • 2 x PCIe 3.0 x1 slots Onboard Graphics • 1 x DVI-D port, supporting a maximum resolution of 1920x1200@60Hz • 1 x DisplayPort, supports a maximum resolution of 4096x2304@24Hz, 2560x1600@60Hz, 3840x2160@60Hz, 1920x1200@60Hz • 1 x HDMI™ port, supports a maximum resolution of 4096x2160@30Hz(7th CPU), 4096x2160@24Hz(6th CPU), 2560x1600@60Hz Multi-GPU • Supports 2-Way AMD® CrossFire™ Technology Storage • Intel® B250 Chipset • 6 x SATA 6Gb/s ports* • 1 x M.2 slot (Key M) - Support up to PCIe 3.0 x4 and SATA 6Gb/s - Supports 2242/ 2260 /2280/ 22110 storage devices - Support PCIe 3.0 x4 NVMe U.2 SSD with Turbo U.2 Host Card** - Intel® Optane™ Memory Ready • Supports Intel® Smart Response Technology for Intel Core™ processors * The SATA1 port will be unavailable when an M.2 SATA SSD module has been installed in the M.2 slot. ** The Turbo U.2 Host Card is not included, please purchase separately. USB • Intel® B250 Chipset - 6 x USB 3.1 Gen1 (SuperSpeed USB) ports (3 Type-A ports + 1 Type-C port on the back panel, 2 ports available through the internal USB

connector) ƒ- 6 x USB 2.0 (High-speed USB) ports (2 Type-A ports on the back panel, 4 ports available through the internal USB connectors) Audio • Realtek® ALC892 Codec - 7.1-Channel High Definition Audio LAN • 1 x Intel® I219-V Gigabit LAN controller Internal I/O Connectors - 1 x 24-pin ATX main power connector - 1 x 8-pin ATX 12V power connector - 6 x SATA 6Gb/s connectors - 1 x M.2 slot - 1 x USB 3.1 Gen1 connector (supports additional 2 USB 3.1 Gen1 ports) - 2 x USB 2.0 connectors (supports additional 4 USB 2.0 ports) - 1 x 4-pin CPU fan connector - 3 x 4-pin system fan connectors - 1 x Front panel audio connector - 2 x Front panel connectors - 1 x Serial port connector - 1 x RGB LED connector - 1 x TPM module connector - 1 x TBT connector - 1 x Chassis Intrusion connector - 1 x Clear CMOS jumper Back Panel I/O Ports - 1 x PS/2 mouse & keyboard combo port - 2 x USB 2.0 ports - 1 x DVI-D port - 1 x DisplayPort - 1 x HDMI™ port - 1 x LAN (RJ45) port - 3 x USB 3.1 Gen1 Type-A ports - 1 x USB 3.1 Gen1 Type-C port - 6 x OFC audio jacks Dimension • 9.6 in. x 9.6 in. (24.4 cm x 24.4 cm) • Micro-ATX Form Factor Mounting • 8 mounting holes 1. Les caractéristiques sont sujettes à certaines modifications sans préavis. Renseignez-vous auprès de votre revendeur afin de connaître les caractéristiques exactes.