

MSI MSI B250M PRO-VH uATX B250 1151 DDR4 SATAIII M.2 USB 3.0

: 71,00€

Déscription du produit

CPU • Supports 6th/7th Gen Intel® Core™ i3/i5/i7 processors, and Intel® Pentium® and Celeron® processors for Socket LGA1151 * This function will be supported depend on the CPU. Chipset • Intel® B250 Chipset Main Memory • 2 x DDR4 memory slots, support up to 32GB - 7th Gen processors support DDR4 2400/2133 MHz* - 6th Gen processors support DDR4 2133 MHz* • Dual channel memory architecture • Supports non-ECC, un-buffered memory • Supports Intel® Extreme Memory Profile (XMP) * Please refer to www.msi.com for more information on compatible memory. ** DDR4 memory modules can only run at maximum of 2400 MHz for 7th Gen processors and 2133 MHz for 6th Gen processors on XMP mode. Slots • 1 x PCIe 3.0 x16 slots • 2 x PCIe 3.0 x1 slots Onboard Graphics • 1 x VGA port, supports a maximum resolution of 2048x1536@50Hz, 2048x1280@60Hz, 1920x1200@60Hz • 1x HDMI™ port, supports a maximum resolution of 4096x2160@30Hz(7th CPU), 4096x2160@24Hz(6th CPU), 2560x1600@60Hz Storage • Intel® B250 Chipset • 6 x SATA 6Gb/s ports • 1 x M.2 slots (Key M)* - Support up to PCIe 3.0 x4 and SATA 6Gb/s - Supports 2242/ 2260/ 2280 storage devices - Intel® Optane™ Memory Ready - Support PCIe 3.0 x4 NVMe U.2 SSD with Turbo U.2 Host card** * The SATA2 port will be unavailable when an M.2 SATA SSD module has been installed in the M.2 slot. ** The Turbo U.2 Host Card is not included, please purchase separately. USB • Intel® B250 Chipset - 6 x USB 3.1 Gen1 (SuperSpeed USB) ports (4 ports on the back panel, 2 ports available through the internal USB connector) • 6 x USB 2.0 (High-speed USB) ports (2 ports on the back panel, 4 ports available through the internal USB connectors) Audio • Realtek® ALC887 Codec - 7.1-Channel High Definition Audio LAN • 1 x Realtek® RTL8111H Gigabit LAN controller Internal I/O Connectors - 1 x 24-pin ATX main

power connector - 1 x 8-pin ATX 12V power connector - 6 x SATA 6Gb/s connectors
- 2 x USB 2.0 connectors (supports additional 4 USB 2.0 ports) - 1 x USB 3.1 Gen1
connector (supports additional 2 USB 3.1 Gen1 ports) - 1 x 4-pin CPU fan connector
- 1 x 4-pin system fan connector - 1 x Front panel audio connector - 2 x Front panel
connectors - 1 x Chassis Intrusion connector - 1 x Serial Port connector - 1 x Clear
CMOS jumper Back Panel I/O Ports - 1 x PS/2 keyboard/ mouse combo port - 2 x
USB 2.0 ports - 1 x HDMI port - 1 x VGA port - 1 x LAN (RJ45) port - 4 x
USB 3.1 Gen1 ports - 3 x audio jacks Dimension • 8.9 in. x 7.3 in. (22.6 cm x 18.5
cm) • Micro-ATX Form Factor Mounting • 6 mounting holes

1. Les caractéristiques sont sujettes à certaines modifications sans préavis.

Renseignez-vous auprès de votre revendeur afin de connaître les caractéristiques exactes.