

ASROCK MSI H110M PRO-VD PLUS M-ATX H110 1151 DDR4 SATAIII USB 3.0

: 67,00€

Déscription du produit

CPU • Supports 6th Gen Intel® Core™ i3/i5/i7 processors, and Intel® Pentium® and Celeron® processors for Socket LGA1151 * Please refer to CPU Support for compatible CPU; the above description is for reference only. Chipset • Intel® H110 Chipset Main Memory • 2 x DDR4 memory slots, support up to 32GB - Supports DDR4 2133 MHz • Dual channel memory architecture • Supports Non-ECC, un-buffered memory • Supports Intel® Extreme Memory Profile (XMP) * Hyper DIMM support is subject to the physical characteristics of individual CPUs * DDR4 2133 MHz and higher memory modules will only run at maximum of DDR4 2133 MHz on XMP mode due to Intel® chipset limitation * Please refer to Compatibility reports for more information of compatible memory. Slots • 1 x PCIe 3.0 x16 slot • 2 x PCIe 2.0 x1 slots Onboard Graphics • 1 x DVI-D port, supports a maximum resolution of 1920x1200@60Hz • 1 x VGA port, supports a maximum resolution of 2048x1536@50Hz, 2048x1280@60Hz, 1920x1200@60Hz On-Board SATA • Intel® H110 Chipset • 4 x SATA 6Gb/s ports USB • Intel® H110 Chipset - 4 x USB 3.1 Gen1 (SuperSpeed USB) ports (2 ports on the back panel, 2 ports available through the internal USB connector) - 6 x USB 2.0 (High-speed USB) ports (2 ports on the back panel, 4 ports available through the internal USB connectors) Audio • Realtek® ALC887 Codec • 7.1-Channel High Definition Audio LAN • 1 x Realtek RTL8111H Gigabit LAN controller Back Panel I/O Ports - 1 x PS/2 mouse port - 1 x PS/2 keyboard port - 2 x USB 2.0 ports - 2 x USB 3.1 Gen1 ports - 1 x DVI-D port - 1 x VGA port - 1 x LAN (RJ45) port - 3 x audio jacks Internal I/O Connectors - 1 x 24-pin ATX main power connector - 1 x 4-pin ATX 12V power connector - 4 x SATA 6Gb/s connectors - 2 x USB 2.0 connectors (supports additional 4 USB 2.0 ports) - 1 x USB 3.1 Gen1 connector (supports additional 2 USB

3.1 Gen1 ports) - 1 x 4-pin CPU fan connector - 1 x 4-pin system fan connectors - 1 x Front panel audio connector - 2 x Front panel connectors - 1 x TPM module connector - 1 x Serial Port connector - 1 x Chassis Intrusion connector - 1 x Clear CMOS jumper Dimension • 8.9 in. x 6.8 in. (22.6 cm x 17.3 cm) Micro-ATX Form Factor Mounting • 6 mounting holes 1. Les caractéristiques sont sujettes à certaines modifications sans préavis. Renseignez-vous auprès de votre revendeur afin de connaître les caractéristiques exactes.