

ASROCK MSI Z270 GAMING M3 ATX Z270 1151 DDR4 SATAIII M.2 USB 3.1

: 167,00€

Déscription du produit

CPU • Supports 6th/7th Gen Intel® Core™ i3/i5/i7 processors, and Intel® Pentium® and Celeron® processors for Socket LGA1151 * This function will be supported depend on the CPU. Chipset • Intel® Z270 Chipset Main Memory • 4 x DDR4 memory slots, support up to 64GB - 7th Gen processors support DDR4 3800(OC)/ 3600(OC)/ 3200(OC)/ 3000(OC)/ 2800(OC)/ 2600(OC)/ 2400/ 2133 MHz* - 6th Gen processors support DDR4 3600(OC)/ 3200(OC)/ 3000(OC)/ 2800(OC)/ 2600(OC)/ 2400(OC)/ 2133 MHz* • Dual channel memory architecture • Supports Intel® Extreme Memory Profile (XMP) * Please refer www.msi.com for more information on compatible memory. Slots • 2 x PCIe 3.0 x16 slots (supports x16/x4 mode)* • 4 x PCIe 3.0 x1 slots * The PCI_E4 slot will be unavailable when an M.2 SSD module has been installed in the M.2_2 slot. Multi-GPU • Supports 2-Way AMD® CrossFire™ Technology Onboard Graphics • 1 x HDMI™ port, supports a maximum resolution of 4096x2160@30Hz(7th CPU), 4096x2160@24Hz(6th CPU), 2560x1600@60Hz • 1 x DVI-D port, supports a maximum resolution of 1920x1200@60Hz Storage • Intel® Z270 Chipset • 6 x SATA 6Gb/s ports* • 2x M.2 slots (Key M) - Support up to PCIe 3.0 x4 and SATA 6Gb/s - Support PCIe 3.0 x4 NVMe U.2 SSD with Turbo U.2 Host Card** - M2_1 slot supports 2242/ 2260 /2280/ 22110 storage devices - M2_2 slot supports 2242/ 2260 /2280 storage devices - Intel® Optane™ Memory Ready for all M.2 slots • Supports Intel® Smart Response Technology for Intel Core™ processors (optional) * M.2 and SATA ports maximum support 2x M.2 PCIe SSDs + 6x SATA HDDs. Please refer to page 33 for M.2 slots with examples of various combination possibilities. ** The Turbo U.2 Host Card is not included, please purchase separately. RAID (optional) • Supports RAID 0, RAID1, RAID 5 and RAID 10 for

SATA storage devices • Supports RAID 0 and RAID1 for M.2 PCIe storage devices* *
M.2 PCIe RAID volume can be created with M.2 GENIE. Please refer to page 42 for details about M.2 GENIE. USB • ASMedia® ASM2142 Chipset - 1 x USB 3.1 Gen2 (SuperSpeed USB 10Gbps) Type-C port on the back panel - 1 x USB 3.1 Gen2 (SuperSpeed USB 10Gbps) Type-A port on the back panel • Intel® Z270 Chipset - 8 x USB 3.1 Gen1 (SuperSpeed USB) ports (4 Type-A ports on the back panel, 4 ports available through the internal USB connector) - 6 x USB 2.0 (High-speed USB) ports (2 ports on the back panel, 4 ports available through the internal USB connector)
Audio • Realtek® ALC1220 Codec - 7.1-Channel High Definition Audio - Supports S/PDIF output LAN • 1 x Killer® E2500 Gigabit LAN controller Internal I/O Connectors - 1 x 24-pin ATX main power connector - 1 x 8-pin ATX 12V power connector - 6 x SATA 6Gb/s connectors - 2 x USB 3.1 Gen1 connectors (supports additional 4 USB 3.1 Gen1 ports) - 2 x USB 2.0 connectors (supports additional 4 USB 2.0 ports) - 1 x 4-pin CPU fan connector - 1 x 4-pin water pump fan connector - 4 x 4-pin system fan connectors - 1 x Front panel audio connector - 2 x Front panel connectors - 1 x LED connector - 1 x TPM module connector - 1 x Chassis Intrusion connector - 1 x Serial connector - 1 x Clear CMOS jumper Back Panel I/O Ports - 1 x PS/2 keyboard/ mouse combo port - 2 x USB 2.0 Type-A ports - 1 x DVI-D port - 1 x USB 3.1 Gen2 Type-A port - 1 x USB 3.1 Gen2 Type-C port - 4 x USB 3.1 Gen1 Type-A ports (optional) - 1 x HDMI® port - 1 x LAN (RJ45) port - 5 x OFC audio jacks - 1 x Optical S/PDIF OUT connector Dimension • 12 in. x 9.6 in. (30.4 cm x 24.3 cm) • ATX Form Factor Mounting • 9 mounting holes 1. Les caractéristiques sont sujettes à certaines modifications sans préavis. Renseignez-vous auprès de votre revendeur afin de connaître les caractéristiques exactes.