

ASROCK MSI Z270 GAMING PLUS ATX Z270 1151 DDR4 SATAIII M.2 USB 3.0

: 141,00€

Déscription du produit

CPU • Supports 7th/6th Gen Intel® Core™ i3/i5/i7 processors, and Intel® Pentium® and Celeron® processors for Socket LGA1151 * This function will be supported depend on the CPU. Chipset • Intel® Z270 Chipset Main Memory • 4 x DDR4 memory slots, support up to 64GB - 7th Gen processors support DDR4 3800(OC)/ 3600(OC)/ 3200(OC)/ 3000(OC)/ 2800(OC)/ 2600(OC)/ 2400/ 2133 MHz* - 6th Gen processors support DDR4 3600(OC)/ 3200(OC)/ 3000(OC)/ 2800(OC)/ 2600(OC)/ 2400(OC)/ 2133 MHz* • Dual channel memory architecture • Supports Intel® Extreme Memory Profile (XMP) * Please refer www.msi.com for more information on compatible memory. Slots • 2 x PCIe 3.0 x16 slots (supports x16/x4 mode) • 4 x PCIe 3.0 x1 slots Multi-GPU • Supports 2-Way AMD® CrossFire™ Technology Onboard Graphics • 1 x VGA port, supports a maximum resolution of 2048x1536@50Hz, 2048x1280@60Hz, 1920x1200@60Hz • 1 x DVI-D port, supports a maximum resolution of 1920x1200@60Hz • 1 x DisplayPort, supports a maximum resolution of 4096x2304@24Hz, 2560x1600@60Hz, 3840x2160@60Hz, 1920x1200@60Hz Storage • Intel® Z270 Chipset • 6 x SATA 6Gb/s ports* • 1x M.2 slots (Key M) - Support up to PCIe 3.0 x4 and SATA 6Gb/s - Support PCIe 3.0 x4 NVMe U.2 SSD with Turbo U.2 Host Card** - Supports 2242/ 2260 /2280/ 22110 storage devices - Intel® Optane™ Memory Ready for all M.2 slots • Supports Intel® Smart Response Technology for Intel Core™ processors * The SATA1 port will become unavailable when M.2 SATA SSD has been installed in M.2 slot. ** The Turbo U.2 Host Card is not included, please purchase separately. ***Intel® Optane™ Technology is only supported when using 7th Gen processors. Before using Intel® Optane™ memory modules, please ensure that you have updated the

drivers and BIOS to the latest version from MSI website. RAID (optional) • Intel® Z270 Chipset • Supports RAID 0, RAID 1, RAID 5 and RAID 10 for SATA storage devices USB • Intel® Z270 Chipset - 8 x USB 3.1 Gen1 (SuperSpeed USB) ports (4 Type-A ports on the back panel, 4 ports available through the internal USB connectors) - 6 x USB 2.0 (High-speed USB) ports (2 Type-A ports on the back panel, 4 ports available through the internal USB connectors) Audio • Realtek® ALC892 Codec - 7.1-Channel High Definition Audio LAN • Intel® I219-V Gigabit LAN controller Internal I/O Connectors - 1 x 24-pin ATX main power connector - 1 x 8-pin ATX 12V power connector - 6 x SATA 6Gb/s connectors - 2 x USB 3.1 Gen1 connectors (supports additional 4 USB 3.1 Gen1 ports) - 2 x USB 2.0 connectors (supports additional 4 USB 2.0 ports) - 1 x 4-pin CPU fan connector - 1 x 4-pin water pump fan connector - 4 x 4-pin system fan connectors - 1 x Front panel audio connector - 2 x Front panel connectors - 1 x TPM module connector - 1 x Chassis Intrusion connector - 1 x Serial port connector - 1 x Parallel port connector - 1 x Clear CMOS jumper Back Panel I/O Ports - 1 x PS/2 mouse & keyboard combo port - 2 x USB 2.0 ports - 1 x VGA port - 1 x DVI-D port - 1 x DisplayPort - 1 x LAN (RJ45) port - 4 x USB 3.1 Gen1 Type-A ports - 6 x OFC audio jacks Dimension • 12.0 in. x 8.9 in. (30.5 cm x 22.5 cm) • ATX Form Factor Mounting • 6 mounting holes 1. Les caractéristiques sont sujettes à certaines modifications sans préavis. Renseignez-vous auprès de votre revendeur afin de connaître les caractéristiques exactes.